

SWITCH TIMERS features

function: switch electric contacts on/off

	standard features	MT - MTS 49	MT - MTS 59	IT 51-52-53- 54 ITS 56-57
1	running times	1-4-6-7-10-15-20-30	30-45-60-90-100-120	6-15-30-60-90-120-180
2	number of poles	on request: 1 or 2 poles	on request: 1 or 2 poles	on request: 1 or 2 poles
3	hold position	on request: optional	on request: optional	on request: optional
4	acoustic signal	Gong: optional	Gong: optional	Long Ring 2.5 sec: optional
5	operating temperature	T 125° C	T 125°C	T 125°C
6	shaft diameter	5-6-7-mm	5-6-7-mm	5-6-7-mm
7	shaft length	on request	on request	on request
8	shaft milling	on request	on request	on request
9	shaft position	on request	on request	on request
10	life cycles	10.000	10.000	10.000
11	AQL	0,65	0,65	0,65
12	accuracy	± 10%	±3%	± 3%
13	load current	16(3)A 250Vac T125°C ENEC 03 13(2)A 250Vac T125°C UL- CSA 15(2)A 120Vac T110°C UL 15(4)A 120Vac T85°C UL	10(2)A 400Vac T125°C ENEC 03 16(3)A 250Vac T125°C ENEC 03 13(2)A 250Vac T110°C UL- CSA 15(2)A 120Vac T110°C UL 15(4)A 120Vac T85°C UL	16(3)A 250Vac T125° ENEC 03 IT 16 (1/4 hp)A UL
14	conformity with	EN 60730-2-1	EN 60730-2-1	EN 60730-2-1
15	APPROVALS	ENEC 03 –UL – CSA	ENEC 03 – UL - CSA	ENEC 03 - UL

CUSTOMIZED PRODUCTS AVAILABLE ON REQUEST